


PRODUCT DATA SHEET

MaxiFlex® Endurance™ 34-847

Colour – Coating	Black
Colour – Liner	Grey
Design	Drivers style knitwrist
Coating	NBR (Nitrile Butadiene Rubber)
Coating texture	Micro-Foam for Controlled Grip
Liner	Nylon, Spandex
Patent number	EP 1 608 808
Palm thickness (mm)	1.10



Dimensions

Size Range	Size 6 (XS)	Size 7 (S)	Size 8 (M)	Size 9 (L)	Size 10 (XL)	Size 11 (XXL)
Total glove length (+/- 10 mm)	250	250	250	250	250	250
Wrist length (mm)			1			
Palm width (mm)	87	90	95	100	104	106
Over lock colour	Blue	Red	Orange	White	Yellow	Black

EN Test Results

Test	Notified body	Result/Pass
EN ISO 21420: 2020	TÜV Rheinland	Yes
EN 388:2016 + A1:2018 M	TÜV Rheinland	4131A



PRODUCT DATA SHEET

MaxiFlex® Endurance™ 34-847

Typical Performance Values

EN ISO 21420: General requirements Dexterity	Level 5
EN 388:2016 + A1:2018 M A. Abrasion Resistance	> 8000 Cycles
EN 388:2016 + A1:2018 M B. Cut Resistance	> 1.2 index
EN 388:2016 + A1:2018 M C. Tear Resistance	> 50 newtons
EN 388:2016 + A1:2018 M D. Puncture Resistance	> 20 newtons
EN 388:2016 + A1:2018 M E. Cut Resistance ISO	≥ 2 Newton

HandCare®

Skin Health Alliance Dermatologically Accredited	Yes
REACH compliant	Yes
Standard 100 by OEKO-TEX® (08.BH.57867 Hohenstein HTTI)	Certified
Washable	60°C/140°F
Sanitized®	Yes



Special features

Touchscreen compatible	Yes
------------------------	-----



PRODUCT DATA SHEET

MaxiFlex® Endurance™ 34-847

Packaging

Pairs per poly bag	12
Poly bags per carton	12
Carton count	144
Carton dimensions (mm)	500 x 295 x 270

Weight

Size Range	Size 6 (XS)	Size 7 (S)	Size 8 (M)	Size 9 (L)	Size 10 (XL)	Size 11 (XXL)
Glove weight / pair (+/- 6 gram)	44	48	52	56	60	64
Gross weight (kg)	7.7	8.3	8.85	9.4	10	10.6
Carton weight (kg)	1	1	1	1	1	1
Net weight (kg)	6.7	7.3	7.9	8.4	9.0	9.6

Issue date: 27/07/2020

